




Fränkische **82820333**

GTIN: 4013960395020

Fränkische alpex tee red. PPSU 20-16-16

alpex



alpex

Die alpex-Familie: Trinkwasserinstallation und Heizungsinstallation mit System

Wer bei der Trinkwasser- und Heizungsinstallation auf Nummer sicher gehen möchte, setzt auf alpex von FRÄNKISCHE. Die einzelnen Komponenten unserer alpex-Familie sind bis ins Detail aufeinander abgestimmt und ergeben ein rundum sicheres System.

82820333

ITEM DETAILS

Reduced tee made of PPSU for drinking water and heating system installations featuring white fixation rings with integrated inspection holes, fixed stainless steel pressing sleeves and leak function. Pressable with pressing contours F and TH.

CHARACTERISTICS

COMMERCIAL DATA

Minimum order quantity	10 Piece
Order step size	10 Piece

FEATURES

Product group	Fitting with 3 connections (EC003025)
Main colour fitting	White
Medium temperature (continuous)	0 - 95 °C
Max. operating pressure at max. medium temperature	10 bar
Material connection 1	Polyphenylsulfone (PPSU)
Material quality connection 1	Other
Surface protection connection 1	Untreated
Surface treatment connection 1	Untreated
Material connection 2	Polyphenylsulfone (PPSU)
Material quality connection 2	Other
Surface protection connection 2	Untreated
Surface treatment connection 2	Untreated
Material connection 3	Polyphenylsulfone (PPSU)
Material quality connection 3	Other
Surface protection connection 3	Untreated
Surface treatment connection 3	Untreated
Model	T-piece

82820333

Nominal diameter connection 1	DN 15
Outer pipe diameter connection 1	20 mm
Wall thickness, connection 1	2.00 mm
Connection 1	Press sleeve
Contour code connection 1	F/TH
Nominal diameter connection 2	DN 12
Outer pipe diameter connection 2	16 mm
Wall thickness, connection 2	2.00 mm
Connection 2	Press sleeve
Contour code connection 2	F/TH
Nominal diameter connection 3	DN 12
Outer pipe diameter connection 3	16 mm
Wall thickness, connection 3	2.00 mm
Connection 3	Press sleeve
Contour code connection 3	F/TH
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)
Length of connection 1	37 mm
Working length connection 1	13 mm
Length of connection 2	37 mm
Working length connection 2	13 mm
Length of connection 3	37 mm
Working length connection 3	13 mm
Max. operating pressure at 20 °C	10 bar
Reducing	Yes
System specific	Yes
With sealing rings/gaskets	Yes

82820333

CUSTOMS

CE Indicator	No
Customs tariff number	Formstucke, Verschlussstücke oder Verbindungsstücke (z.B. Kniestücke, Flansche), aus Kunststoffen (39174000)

LOGISTICS

Delivery time (working days)	15 Days
------------------------------	---------

OTHER

Contains battery	No
REACH Indicator	No
Unlimited shelf life	Yes

MORE PICTURES



82820333

