



Fränkische

82840350

GTIN: 4013960397703

Fränkische alpex L tee red. PPSU duo XS 40-20-40

alpex L



alpex L

Mehrschichtverbundrohrsystem für die Trinkwasser- und Heizungsinstallation in den großen Dimensionen 40-75

- Mit Leckagefunktion - Großes Sichtfenster zur Einsteckkontrolle - Strömungsoptimiert - Fittings aus Kunststoff PPSU und entzinkungsbeständigem Messing - Doppelte Sicherheit durch 2 O-Ringe - Optimale Ergänzung zu alpex F50 PROFi

82840350

ITEM DETAILS

Reduced tee made of PPSU for drinking water and heating system installations featuring white fixation rings with integrated inspection holes, fixed stainless steel pressing sleeves and leak function. Can be pressed using the F-contour, the dimensions smaller than or equal to 32 mm also with the TH pressing contour.

CHARACTERISTICS

COMMERCIAL DATA

Minimum order quantity	3 Piece
Order step size	3 Piece

FEATURES

Product group	Fitting with 3 connections (EC003025)
Main colour fitting	White
Medium temperature (continuous)	0 - 95 °C
Max. operating pressure at max. medium temperature	10 bar
Material connection 1	Polyphenylsulfone (PPSU)
Material quality connection 1	Other
Surface protection connection 1	Untreated
Surface treatment connection 1	Untreated
Material connection 2	Polyphenylsulfone (PPSU)
Material quality connection 2	Other
Surface protection connection 2	Untreated
Surface treatment connection 2	Untreated
Material connection 3	Polyphenylsulfone (PPSU)
Material quality connection 3	Other
Surface protection connection 3	Untreated
Surface treatment connection 3	Untreated

82840350

Model	T-piece
Nominal diameter connection 1	DN 32
Outer pipe diameter connection 1	40 mm
Wall thickness, connection 1	3.50 mm
Connection 1	Press sleeve
Contour code connection 1	F
Nominal diameter connection 2	DN 15
Outer pipe diameter connection 2	20 mm
Wall thickness, connection 2	2.00 mm
Connection 2	Press sleeve
Contour code connection 2	F/TH
Nominal diameter connection 3	DN 32
Outer pipe diameter connection 3	40 mm
Wall thickness, connection 3	3.50 mm
Connection 3	Press sleeve
Contour code connection 3	F
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)
Length of connection 1	57 mm
Working length connection 1	17 mm
Length of connection 2	50 mm
Working length connection 2	25 mm
Length of connection 3	57 mm
Working length connection 3	17 mm
Max. operating pressure at 20 °C	10 bar
Reducing	Yes
System specific	Yes

82840350

With sealing rings/gaskets	Yes
----------------------------	-----

CUSTOMS

CE Indicator	No
Customs tariff number	Formstücke, Verschlussstücke oder Verbindungsstücke (z.B. Kniestücke, Flansche), aus Kunststoffen (39174000)

LOGISTICS

Delivery time (working days)	15 Days
------------------------------	---------

OTHER

Contains battery	No
REACH Indicator	No
Unlimited shelf life	Yes

MORE PICTURES



82840350

