



Fränkische

82840370

GTIN: 4013960397727

Fränkische alpex L tee red. PPSU duo XS 40-32-40

alpex L



alpex L

Mehrschichtverbundrohrsystem für die Trinkwasser- und Heizungsinstallation in den großen Dimensionen 40-75

- Mit Leckagefunktion - Großes Sichtfenster zur Einsteckkontrolle - Strömungsoptimiert - Fittings aus Kunststoff PPSU und entzinkungsbeständigem Messing - Doppelte Sicherheit durch 2 O-Ringe - Optimale Ergänzung zu alpex F50 PROFi

82840370

ITEM DETAILS

Reduced tee made of PPSU for drinking water and heating system installations featuring white fixation rings with integrated inspection holes, fixed stainless steel pressing sleeves and leak function. Can be pressed using the F-contour, the dimensions smaller than or equal to 32 mm also with the TH pressing contour.

CHARACTERISTICS

COMMERCIAL DATA

Minimum order quantity	3 Piece
Order step size	3 Piece

FEATURES

Product group	Fitting with 3 connections (EC003025)
Main colour fitting	White
Medium temperature (continuous)	0 - 95 °C
Max. operating pressure at max. medium temperature	10 bar
Material connection 1	Polyphenylsulfone (PPSU)
Material quality connection 1	Other
Surface protection connection 1	Untreated
Surface treatment connection 1	Untreated
Material connection 2	Polyphenylsulfone (PPSU)
Material quality connection 2	Other
Surface protection connection 2	Untreated
Surface treatment connection 2	Untreated
Material connection 3	Polyphenylsulfone (PPSU)
Material quality connection 3	Other
Surface protection connection 3	Untreated
Surface treatment connection 3	Untreated

82840370

Model	T-piece
Nominal diameter connection 1	DN 32
Outer pipe diameter connection 1	40 mm
Wall thickness, connection 1	3.50 mm
Connection 1	Press sleeve
Contour code connection 1	F
Nominal diameter connection 2	DN 25
Outer pipe diameter connection 2	32 mm
Wall thickness, connection 2	3.00 mm
Connection 2	Press sleeve
Contour code connection 2	F/TH
Nominal diameter connection 3	DN 32
Outer pipe diameter connection 3	40 mm
Wall thickness, connection 3	3.50 mm
Connection 3	Press sleeve
Contour code connection 3	F
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)
Length of connection 1	64 mm
Working length connection 1	24 mm
Length of connection 2	59 mm
Working length connection 2	25 mm
Length of connection 3	64 mm
Working length connection 3	24 mm
Max. operating pressure at 20 °C	10 bar
Reducing	Yes
System specific	Yes

82840370

With sealing rings/gaskets

Yes

CUSTOMS

CE Indicator

No

Customs tariff number

Formstücke, Verschlussstücke oder
Verbindungsstücke (z.B. Kniestücke,
Flansche), aus Kunststoffen (39174000)

LOGISTICS

Delivery time (working days)

15 Days

OTHER

Contains battery

No

REACH Indicator

No

Unlimited shelf life

Yes

MORE PICTURES



82840370

