



Fränkische

86740742

GTIN: 4013960152807

Fränkische alpex L tee with FT 40-Rp1/2-40

alpex L



alpex L

Mehrschichtverbundrohrsystem für die Trinkwasser- und Heizungsinstallation in den großen Dimensionen 40-75

- Mit Leckagefunktion - Großes Sichtfenster zur Einsteckkontrolle - Strömungsoptimiert - Fittings aus Kunststoff PPSU und entzinkungsbeständigem Messing - Doppelte Sicherheit durch 2 O-Ringe - Optimale Ergänzung zu alpex F50 PROFIL

86740742

ITEM DETAILS

Female thread tee adapter according to DIN EN 10226-1 made of dezincification-resistant brass for drinking water and heating system installations featuring white fixation rings with integrated inspection holes, fixed stainless steel pressing sleeves and leak function. Pressable with pressing contour F.

CHARACTERISTICS

COMMERCIAL DATA

Minimum order quantity	3 Piece
Order step size	3 Piece

FEATURES

Product group	Fitting with 3 connections (EC003025)
Main colour fitting	Brass
Medium temperature (continuous)	0 - 95 °C
Max. operating pressure at max. medium temperature	10 bar
Material connection 1	Brass
Material quality connection 1	CuZn36Pb-C (CC770S)
Surface protection connection 1	Untreated
Surface treatment connection 1	Untreated
Material connection 2	Brass
Material quality connection 2	CuZn36Pb-C (CC770S)
Surface protection connection 2	Untreated
Surface treatment connection 2	Untreated
Material connection 3	Brass
Material quality connection 3	CuZn36Pb-C (CC770S)
Surface protection connection 3	Untreated
Surface treatment connection 3	Untreated

86740742

Model	T-piece
Nominal diameter connection 1	DN 32
Outer pipe diameter connection 1	40 mm
Wall thickness, connection 1	3.50 mm
Connection 1	Press sleeve
Contour code connection 1	F
Nominal diameter connection 2	DN 15
Connection 2	Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1)
Nominal diameter connection 3	DN 32
Outer pipe diameter connection 3	40 mm
Wall thickness, connection 3	3.50 mm
Connection 3	Press sleeve
Contour code connection 3	F
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)
Length of connection 1	69 mm
Working length connection 1	28 mm
Length of connection 2	36 mm
Working length connection 2	23 mm
Length of connection 3	69 mm
Working length connection 3	28 mm
Max. operating pressure at 20 °C	10 bar
Reducing	Yes
System specific	Yes
With sealing rings/gaskets	Yes

86740742

CUSTOMS

CE Indicator	No
Customs tariff number	Rohrformstücke, Rohrverschlussstücke und Rohrverbindungsstücke (z.B. Bogen, Muffen), aus Kupferlegierungen (74122000)

LOGISTICS

Delivery time (working days)	15 Days
------------------------------	---------

OTHER

Contains battery	No
ECHA DB Scip ID	38751d69-c49b-44a5-ad7f-6d7e469c746e
REACH Indicator	No
Unlimited shelf life	Yes

MORE PICTURES



86740742

