

Domestic hot water circulators

The Wilo-Yonos PICO-Z will be replacing the Wilo SB 30.



The SB 30, a fixed speed secondary hot water circulator, will be discontinuing in 2025.

The Wilo-Yonos PICO-Z, an energy efficient alternative which has the option for differential pressure, will become its direct replacement.

The Wilo-Yonos PICO-Z is compact, easy to install has stainless steel housing and comes with its own insulation shell.

Suitable for domestic and light commercial applications.



	 NEW Wilo Yonos-PICO-Z 6m 4255416	 OLD Wilo SB 30 4035479
Port-to-port length	130mm	130mm
Energy consumption	4 - 40 W	89 W
Max delivery head	6m	5m
Max. volume flow	3.5 m ³ /h	4.3 m ³ /h
Control mode	Constant differential pressure Constant speed 3 curves constant speed	None
Setting option	Continuous 3 curves for constant speed	Three set speeds
Venting	Manual via button Automatic venting and deblocking	Manual via centre screw
Display	LED display	None
Fluid temperature range	+2°C to +95 °C	+2 °C to +65 °C
Parameter indication	Q volume flow in m ³ /h P power in W	None

Contact us:

Email: sales.uk@wilo.com

Phone: 01283 523000

www.wilo.co.uk