

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: PENOSIL NEUTRAL SILICONE 317

Other means of identification:
Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:
Relevant uses (Consumer use): Sealant
Relevant uses (Professional users): Sealant
Relevant uses (Industrial user): Sealant
Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:
WOLF GROUP IBERICO S.A.U
AVDA. BERTRAN GÜELL, 78
08850 GAVÀ - BARCELONA - SPAIN
Phone: +34 936629911
QHSE.es@wolf-group.com
www.wolf-group.com

1.4 Emergency telephone number: 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Warning



Hazard statements:
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.

Precautionary statements:
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P261: Avoid breathing vapours
P264: Wash thoroughly after use.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501: Dispose of the contents and/or its container using the separate collection system in your municipality.

Supplementary information:
EUH066: Repeated exposure may cause skin dryness or cracking.
Contains Butan-2-one O,O',O''-(vinylsilylidene)trioxime.

Substances that contribute to the classification
N-(3-(trimethoxysilyl)propyl)ethylenediamine

2.3 Other hazards:
Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Mixture composed of chemical products**Components:**

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 917-488-4 EC: 01-2119458943-27-XXXX REACH: 2224-33-1 218-747-8 01-2119970537-27-XXXX	Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1: H304; EUH066 - Danger Butan-2-one O,O',O''-(vinylsilylidene)trioxime Eye Dam. 1: H318; Skin Sens. 1B: H317; STOT RE 2: H373 - Danger	 10 - <20 %
CAS: 58190-57-1 611-631-1 EC: 01-2119982962-22-XXXX	2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] STOT RE 2: H373 - Warning	 1 - <2,5 %
CAS: 1760-24-3 217-164-6 EC: 01-2119970215-39-XXXX	N-(3-(trimethoxysilyl)propyl)ethylenediamine Acute Tox. 4: H332; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1A: H317; STOT RE 2: H373 - Danger	 0,1 - <1 %
CAS: 1333-86-4 215-609-9 EC: 01-2119384822-32-XXXX	Carbon black Carc. 2: H351 - Warning	 0,1 - <1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 5: FIREFIGHTING MEASURES (continued)

5.1 Extinguishing media:**Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages: Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 7: HANDLING AND STORAGE (continued)

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification		Occupational exposure limits	
Carbon black	WEL (8h)	3.5 mg/m ³	
CAS: 1333-86-4	WEL (15 min)	7 mg/m ³	

DNEL (Workers):

Identification	Short exposure		Long exposure	
	Systemic	Local	Systemic	Local
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1 EC: 218-747-8	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0.15 mg/kg
	Inhalation	Not relevant	Not relevant	1.06 mg/m ³
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] CAS: 58190-57-1 EC: 611-631-1	Oral	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0.059 mg/kg
	Inhalation	Not relevant	Not relevant	0.419 mg/m ³

DNEL (General population):

Identification	Short exposure		Long exposure	
	Systemic	Local	Systemic	Local
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1 EC: 218-747-8	Oral	Not relevant	Not relevant	0.075 mg/kg
	Dermal	Not relevant	Not relevant	0.075 mg/kg
	Inhalation	Not relevant	Not relevant	0.26 mg/m ³
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] CAS: 58190-57-1 EC: 611-631-1	Oral	Not relevant	Not relevant	0.03 mg/kg
	Dermal	Not relevant	Not relevant	0.03 mg/kg
	Inhalation	Not relevant	Not relevant	0.103 mg/m ³

PNEC:

Identification				
	STP	4.06 mg/L	Fresh water	0.019 mg/L
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1 EC: 218-747-8	Soil	133.8 mg/kg	Marine water	0.002 mg/L
	Intermittent	Not relevant	Sediment (Fresh water)	1136.562 mg/kg
	Oral	0.003333 g/kg	Sediment (Marine water)	113.656 mg/kg

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification					
2-Propanone, 2,2',2''-[O,O',O'']-(ethylsilylidene)trioxime] CAS: 58190-57-1 EC: 611-631-1	STP	2.398 mg/L	Fresh water	0.24 mg/L	
	Soil	240.95 mg/kg	Marine water	0.024 mg/L	
	Intermittent	Not relevant	Sediment (Fresh water)	2047.053 mg/kg	
	Oral	0.002638 g/kg	Sediment (Marine water)	204.705 mg/kg	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	STP	25 mg/L	Fresh water	0.062 mg/L	
	Soil	0.009 mg/kg	Marine water	0.006 mg/L	
	Intermittent	0.62 mg/L	Sediment (Fresh water)	0.22 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0.022 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 0.63 % weight
V.O.C. density at 20 °C: 8.76 kg/m³ (8.76 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Paste
Colour:	Not relevant *
Odour:	Not relevant *
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	202 °C
Vapour pressure at 20 °C:	27 Pa
Vapour pressure at 50 °C:	131.67 Pa (0.13 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1396.7 kg/m ³
Relative density at 20 °C:	1.2
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	>20.5 mm ² /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	301 °C
Lower flammability limit:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Upper flammability limit: Not relevant *

Particle characteristics:

Median equivalent diameter: Not relevant *

9.2 Other information:**Information with regard to physical hazard classes:**

Explosive properties: Not relevant *

Oxidising properties: Not relevant *

Corrosive to metals: Not relevant *

Heat of combustion: Not relevant *

Aerosols-total percentage (by mass) of flammable components: Not relevant *

Other safety characteristics:

Surface tension at 20 °C: Not relevant *

Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
- IARC: Carbon black (2B); Toluene (3); propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1 EC: 218-747-8	LD50 oral	3519 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics CAS: Not relevant EC: 917-488-4	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] CAS: 58190-57-1 EC: 611-631-1	LD50 oral	2500 mg/kg	Rat
	LD50 dermal	2493 mg/kg	Rat
	LC50 inhalation vapour	>20 mg/L	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	LD50 oral	2295 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	11 mg/L	
Carbon black CAS: 1333-86-4 EC: 215-609-9	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation dust	>5 mg/L	

Acute Toxicity Estimate (ATE mix):

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	0 %
Dermal	>2000 mg/kg (Calculation method)	0 %
LC50 inhalation vapour	>20 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1	LC50	55000 mg/L (96 h)	QSAR	Fish
	EC50	17168 mg/L (48 h)	QSAR	Fish
	EC50	1429 mg/L (96 h)	QSAR	Fish
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] CAS: 58190-57-1	LC50	697 mg/L (96 h)	Pimephales promelas	Fish
	EC50	679 mg/L (48 h)	N/A	Crustacean
	EC50	315 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Carbon black CAS: 1333-86-4	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	5600 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Not relevant		

Chronic toxicity:

Identification	Concentration		Species	Genus
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1	NOEC	50 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1 EC: 218-747-8	BOD5	Not relevant	Concentration	20 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	0 %
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	BOD5	Not relevant	Concentration	10.7 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	39 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
Butan-2-one O,O',O''-(vinylsilylidene)trioxime CAS: 2224-33-1 EC: 218-747-8	BCF	1	
	Pow Log	0.6	
	Potential	Low	
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] CAS: 58190-57-1 EC: 611-631-1	BCF		
	Pow Log	9.83	
	Potential		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-Propanone, 2,2',2''-[O,O',O''-(ethylsilylidene)trioxime] CAS: 58190-57-1	Koc	85500	Henry	Not relevant
	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Absorption/desorption		Volatility	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	Koc	0.2	Henry	0E+0 Pa·m ³ /mol	
	Conclusion	Very High	Dry soil	Not relevant	
	Surface tension	Not relevant	Moist soil	Not relevant	

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09	Non-hazardous

Type of waste:

Not relevant

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Not relevant

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

- CONTINUED ON NEXT PAGE -

Safety data sheet

According to UK REACH (S.I. 2019/758)

PENOSIL NEUTRAL SILICONE 317

SECTION 15: REGULATORY INFORMATION (continued)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Acute Tox. 4: H332 - Harmful if inhaled.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 2: H351 - Suspected of causing cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Classification procedure:

Skin Sens. 1A: Calculation method

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD₅: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD₅₀: Lethal Dose 50

LC₅₀: Lethal Concentration 50

EC₅₀: Effective concentration 50

LogPO_W: Octanol/water partition coefficient

K_{oc}: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -